

DECLARATION OF PERFORMANCE according to Annex III of the Regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No 574/201

No. 20175 Unique identification code of the product-type: RM20				
Product for Structural and non structural repair for concrete				
Applying mortar by hand (3.1)				
Recasting with concrete (3.2)				
Spraying concrete or mortar (3.3)				
Structural strengthening by adding mortar or concrete (4.4)				
Increasing cover to reinforcement with additional cementitious mortar or concrete (7.1 Replacing contaminated concrete (7.2))			
lanufacturer:				
PAGEL Spezial-Beton GmbH & Co. KG				
Wolfsbankring 9				
45355 Essen				
Germany				
ystem/s of AVCP:				
System 2+ (for uses in buildings and civil engineering works)				
System 3 (for uses subject to reaction to fire regulations)				
armonised standard:				
EN 1504-3:2005				
otified body/ies: Qualitätsgemeinschaft Deutsche Bauchemie e.V., identification no. 0921 MPA Bau Hannover, identification no. 0764				



Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification	
Compressive strength	R4	System 2+		
Chloride ion content ¹⁾	≤ 0,05 %	System 2+		
Adhesive bond	≥ 2,0 MPa	System 2+		
Restrained shrinkage/expansion ²⁾	≥ 2,0 MPa	System 2+		
Carbonation resistance ^{1) 3)}	passed	System 2+		
Elastic modulus	≥ 20 GPa	System 2+	EN 1504-3:2005	
Thermal compatibility	NPD	System 2+	EIN 1504-5.2005	
Skid Resistance	NPD	System 2+		
Coefficient of thermal expansion ⁴⁾	NPD	System 2+		
Capillary absorption	NPD	System 2+		
Reaction to fire ⁵⁾	A1	System 3		
Dangerous substances	NPD	System 2+		

Declared performance/s:

1) Only relevant for repair of reinforced concrete.

2) Not required if thermal cycling is undertaken.

3) Not required if the repair product includes a surface protection system with proven protection against carbonation (EN 1504-2) or is a PC mortar.

- 4) Relevant to PC only.
- 5) Also possible A1, A2, B, C and D, whereby the last four classes in Germany for the time being need an approval from DIBt. The possible class F is not admitted in Germany. This class means in Germany "readily flammable". In other European MS this class means "no performance determined" (NPD)" and is admitted with consideration of the valid regulation in the respective MS.

NPD = no performance determined

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Daniel Schempershofe, head of quality control and product development

Essen, 30.11.2016

D. Schempershafe